

					
製品	CV420-30X	CV355-30X-IP	CV355-30X-NDI	CV420-30X-IP	CV420-30X-NDI
12G/6G/3G-SDI	<input checked="" type="checkbox"/>				
3G-SDI	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		
HDMI	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<b>NDI</b>			<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
IPコーデックすべて	HEVC, SRT, UDP, DHCP, MPEG-TS, RTSP, RTP, RTMP, RTMPS, DNS, HTTP, HTTPS, IPv4, NTP, TCP, 802.1X				
UHD	<input checked="" type="checkbox"/>			<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
HD	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
解像度	3840x2160p60fps, 1920x1080p, 1920x1080i, 1280x720p まで	1920x1080p60fps, 1920x1080i, 1280x720p まで	1920x1080p60fps, 1920x1080i, 1280x720p まで	3840x2160p60fps, 1920x1080p, 1920x1080i, 1280x720p まで	3840x2160p60fps, 1920x1080p, 1920x1080i, 1280x720p まで
光学ズーム	30x (4.6~135mm)	30x (4.6~135mm)	30x (4.6~135mm)	30x (4.6~135mm)	30x (4.6~135mm)
最大画角	水平 70°	水平 70°	水平 70°	水平 70°	水平 70°
センサーの種類	8.5 メガピクセル 1/2.5"	8.5 メガピクセル 1/2.5"	8.5 メガピクセル 1/2.5"	8.5 メガピクセル 1/2.5"	8.5 メガピクセル 1/2.5"
PoE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
最小オブジェクト距離	1.5m	1.5m	1.5m	1.5m	1.5m
寸法	67 x 67 x 223 mm	67 x 67 x 190 mm	67 x 67 x 190 mm	67 x 67 x 190 mm	67 x 67 x 190 mm
重量	0.82 kg	0.70 kg	0.70 kg	0.68 kg	0.68 kg